

FABRIJET

FD-1908

1,9m DIRECT TEXTILE PRINTER



FABRIJET
FD-1908

Print Speed	185m ² /hr	95m ² /hr	65m ² /hr
Print Resolution	600 x 600dpi 1Pass	600 x 1,200dpi 2Pass	600 x 1,800dpi 3Pass
Max Print Width	1,880mm		
Max Media Width	1,900mm		
Print Mode	Bi-Direction / Uni-Direction , Normal / Interleave		
Printhead	Kyocera printhead (8 heads)		
Color	8 Colors		
Ink	DGI original water based Reactive / Pigment ink		
Interface	TCP / IP		
Environmental Range	Temperature : 22.5~27.5°C Humidity : 40~70% Environment condition may affect on final printing quality.		
Electricity Requirements	Printer : 200~240V/11A	Dryer : 3Phase 380V/40A	

※ All specifications are subject to change without notice.

Dimension for Installation

	Uncrated				Crated			
	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
Printer	4,410	1,820	2,080	1,630	4,700	2,000	2,150	2,400
Dryer	3,720	1,500	1,600	1,265	4,000	1,800	1,850	1,700

